

UPTON **AUTOMOTIVE** **GEAR OIL** **EPA**

High Quality Lubricants



Distributor Tunggal
PT. SOKKA MULIA ABADI
e-mail : sokkamulia@uptonlube.com
www.uptonlube.com

High Performance Automotive Gear OIL

It is recommended for lubricants in heavy duty gears for gears or transmissions in motorized vehicles, for automatic transmission units operating under high speed conditions with shock loads and high speeds.

UPTON EPA					
Characteristics	ASTM	90 GL4	90 GL5	140 GL4	140 GL5
Density at 15°C/kg/l	D1298	0.896	0.896	0.904	0.904
Kinematic Viscosity 40°C cSt	D445	173.5	173.5	332	327
Kinematic Viscosity 100°C cSt	D445	17.97	17.98	28.5	27.2
Viscosity Index	D2270	114	114	106	111
Flash Point	D92	238	214	254	254
Foaming Characteristic	D892				
Sequence I		0/0	0/0	0/0	0/0
Sequence II		0/0	0/0	0/0	0/0
Sequence III		0/0	0/0	0/0	0/0

UPTON LUBRICANTS

Manufactured Under ISO 9001-2015
Quality Management System BVQI No. 235093
Produced By :
PT. AMAN PELUMAS NUSANTARA
SFB Blok MM No. 16 Kawasan Industri
Jababeka Tahap II Cikarang Bekasi - 17530

