

UPTON

APN GEAR

Industrial Gear Oil

High Performance



Distributor Tunggal
PT. SOKKA MULIA ABADI
e-mail : sokkamulia@uptonlube.com
www.uptonlube.com

UPTON LUBRICANTS

Manufactured Under ISO 9001-2015
Quality Management System BVQI No. 235093
Produced By :
PT. AMAN PELUMAS NUSANTARA
SFB Blok MM No. 16 Kawasan Industri
Jababeka Tahap II Cikarang Bekasi - 17530

Description

The premium quality gear oil formulated with quality base oil incorporating various additives such as special extreme pressure additives, oxidation inhibitor, rust prevention additive, anti-foaming and oiliness agents to provide excellent performance.

Application

Recommended for use on steel gears, suitable for industrial gears that require extreme pressure (EP) performance, Other applications are suitable for lubricated circulating and splash systems.

Characteristics

1. High VI And Extremely Low Pour Point.
2. Good Oxidation Stability - oxidation stability under severe/ high temperature operating condition and assures longer oil life.
3. Good Anti-Pitting, Anti-Wear & Anti-Seizure Properties - Addition of special oiliness and extreme pressure agents give this oil excellent anti-pitting, anti-wear & anti-seizure properties which help to extend gear service life.
4. Good Demulsibility - Extremely quick separation with water prevents formation of sludge and rust.
5. Good Anti-Corrosion & Anti-Rust Properties - Effective rust preventive agent and corrosion inhibitor prevent corrosion caused by water and acid produced through deterioration process.

APN GEAR OIL - SERIES

Characteristics	ASTM	150	220	320	460
ISO VG		150	220	320	460
Density at 15°C/kg/l	D1298	0.876	0.887	0.896	0.903
Kinematic Viscosity 40°C cSt	D445	149	220	315	424
Kinematic Viscosity 100°C cSt	D445	15	19	26	29
Viscosity Index	D2270	101	98	97	96
Flash Point	D92	225	230	240	240
Pour Point ,°C	D97	-12	-12	-11	-10
Foaming Characteristic	D892				
Sequence I		0/0	0/0	0/0	0/0
Sequence II		0/0	0/0	0/0	0/0
Sequence III		0/0	0/0	0/0	0/0

