



UPTON

POLYUREASE GREASE

NLGI 2,3

High Performance Grease



Distributor Tunggal
PT. SOKKA MULIA ABADI
e-mail : sokkamulia@uptonlube.com
www.uptonlube.com

UPTON LUBRICANTS

Manufactured Under ISO 9001-2015
Quality Management System BVQI No. 235093
Produced By :
PT. AMAN PELUMAS NUSANTARA
SFB Blok MM No. 16 Kawasan Industri
Jababeka Tahap II Cikarang Bekasi - 17530

DESCRIPTION AND FEATURES

UPTON POLYUREA GREASE provides over 270 oC dropping point, and can not be softened in high temperature of 200 oC and maintain permanent lubricating properties. Specially, reuse POLYUREA also displays excellent function in resting water scour.

UPTON POLYUREA GREASE			
Characteristics	ASTM	POLYUREA 2	POLYUREA 3
NLGI GRADE	Grade	2	3
Soap Type		Polyurea	Polyurea
Color	Visual	Green	Green
Dropping Point, ?°C	D 2265	270	270
Water washout, %los max	D 1264	1.0	1.0
Base Oil Viscosity, @40°C	D 445	220	220
Copper corrosion 100°C(24 hours)	D 4048	1b	1b
Penetration (1/10mm)	D 217	265~ 295	220 ~ 250
Timken OK Loading	D 2509	=90lb	=90lb
Four Ball Wear, Scar mm	D 2266	0.5	0.5
Rust Prevention	D 1743	Pass	Pass
Four Ball EP ,Weld Point	D 2596	=400	=400

