

PTFE GREASE GREASE

APPLICATIONS

This grease is recommended for use in high speed bearings ,whose function is to reduce friction, wear , prevent corrosion, control temperature and transmit power.

UPTONE PTFE GREASE		
Characteristics	ASTM	PTFE
NLGI GRADE	Grade	2
Soap Type		Lithium Complex
Color	Visual	Pure white
Dropping Point, ?	D 2265	>300
Penetration (1/10mm)	D 217	265~295
Four Ball Wear, Scar mm	D 2266	0.485
Four Ball EP ,Weld Point	D 2596	800
Oil separation.% by mass	D 6184	4.01%
Water washout, %loss 1hr,78°C,600rpm	D 1264	0.02%
Water spray,%loss1min,38°C,276kPa	D 4049	0.01%
Vaporation Loss, %loss	D 972	0.001%
Copper Corrosion24hr,100°C	D 4048	1a

UPTON PTFE GREASE

NLGI #2

High Performance Grease



Distributor Tunggal
PT. SOKKA MULIA ABADI
e-mail : sokkamulia@uptonlube.com
www.uptonlube.com

UPTON LUBRICANTS

Manufactured Under ISO 9001-2015
Quality Management System BVQI No. 235093
Produced By :
PT. AMAN PELUMAS NUSANTARA
SFB Blok MM No. 16 Kawasan Industri
Jababeka Tahap II Cikarang Bekasi - 17530

