



UPTON
FRICITION S3 4T
SAE 10W-40
API SERVICE SL
JASO MB

Distributor Tunggal
PT. SOKKA MULIA ABADI
e-mail : sokkamulia@uptonlube.com
www.uptonlube.com

Sole Agent

Characteristics	S3 4T 10W40 SL/MA
Density at 15°C/kg/l	0.860
Kinematic Viscosity 40°C cSt	93.5
Kinematic Viscosity 100°C cSt	14.18
Viscosity Index	156
Flash Point	234
Pour Point ,°C	-36
Base Number (TBN)	5.2
Foaming Characteristic	
Sequence I	0/0
Sequence II	0/0
Sequence III	0/0

Specification & Performance

API SL, JASO MB

Manufactured Under ISO 9001-2015

Quality Management System BVQI No. 235093

Produced By :

PT. AMAN PELUMAS NUSANTARA
SFB Blok MM No. 16 Kawasan Industri
Jababeka Tahap II Cikarang Bekasi - 17530



UPTON FRICTION S3 4T
SAE 10W-40
API SERVICE SL
JASO MA

UPTON FRICTION S3 4T adalah pelumas mesin sepeda motor 4T diformulasi dengan paket aditif lengkap untuk melindungi mesin dari keausan dan korosi.

UPTON FRICTION S3 4T didisain untuk menjaga kebersihan mesin dan mencegah slip kopling dan deposit pada piston.

UPTON FRICTION S3 4T sangat handal digunakan untuk mesin modern dan klasik

