

UPTON MATIC S3

SAE 10W-40
API SERVICE SL
JASO MB



Distributor Tunggal
PT. SOKKA MULIA ABADI
e-mail : sokkamulia@uptonlube.com
www.uptonlube.com

Sole Agent

Characteristics	MATIC S3 10W40 SL/MB
Density at 15°C/kg/l	0.866
Kinematic Viscosity 40°C cSt	93.6
Kinematic Viscosity 100°C cSt	14.25
Viscosity Index	157
Flash Point	238
Pour Point , °C	-39
Base Number (TBN)	5.2
Foaming Characteristic	
Sequence I	0/0
Sequence II	0/0
Sequence III	0/0

Specification & Performance

API SL, JASO MB

Manufactured Under ISO 9001-2015
Quality Management System BVQI No. 235093

Produced By :
PT. AMAN PELUMAS NUSANTARA
SFB Blok MM No. 16 Kawasan Industri
Jababeka Tahap II Cikarang Bekasi - 17530



UPTON MATIC S3
SAE 10W-40 API SERVICE SL
JASO MB

UPTON MATIC S6 adalah pelumas mesin sepeda motor matic yang mengandung aditif Molybdenum (Mo) untuk meminimalkan gesekan mesin pada suhu dan kecepatan tinggi

UPTON MATIC S6 memberikan unjuk kerja yang memenuhi persyaratan pabrikan kendaraan, cocok untuk penggunaan sehari-hari yang mengutamakan perlindungan mesin dan konsumsi bahan bakar yang optimal

1,0L
0,8L

