

UPTON MATIC S6

SAE 20W-50
API SERVICE SJ
JASO MB



Distributor Tunggal
PT. SOKKA MULIA ABADI
e-mail : sokkamulia@uptonlube.com
www.uptonlube.com

Sole Agent

Characteristics	MATIC S6 20W50 SJ /MB
Density at 15°C/kg/l	0.883
Kinematic Viscosity 40°C cSt	179.1
Kinematic Viscosity 100°C cSt	21.53
Viscosity Index	139
Flash Point	250
Pour Point ,°C	-24
Base Number (TBN)	5.2
Foaming Characteristic	
Sequence I	0/0
Sequence II	0/0
Sequence III	0/0

Specification & Performance

API SJ, JASO MB

Manufactured Under ISO 9001-2015

Quality Management System BVQI No. 235093

Produced By :

PT. AMAN PELUMAS NUSANTARA

SFB Blok MM No. 16 Kawasan Industri

Jababeka Tahap II Cikarang Bekasi - 17530



UPTON MATIC S6

SAE 20W-50 API SERVICE SJ
JASO MB

UPTON MATIC S6 adalah pelumas mesin sepeda motor matic yang mengandung aditif Molybdenum (Mo) untuk meminimalkan gesekan mesin pada suhu dan kecepatan tinggi

UPTON MATIC S6 memberikan unjuk kerja yang memenuhi persyaratan pabrik kendaraan, cocok untuk penggunaan sehari-hari yang mengutamakan perlindungan mesin dan konsumsi bahan bakar yang optimal

